



MILTON ROY

USA

DeGassing Valves

- ASSISTS IN PURGING GAS FROM GAS-BEARING LIQUIDS IN PUMPING OPERATIONS
- FITS INTO LIQUID END TO PURGE GAS BEFORE IT IS PUMPED
- FITS IN BETWEEN HEAD AND CHECK VALVE
- RUGGED PVC CONSTRUCTION



- Automatically bleeds off gases to prevent operator from manual bleed operations
- Prevents pump from vapor locking and increases reliability of diaphragm metering pumps used in gas-bearing liquid conveyance applications
- Kits available for Special and Unique Applications
- Excellent for sodium hypochlorite and other gas-bearing liquid applications (PVC only)



**DeGassing Valve only available in PVC Standard
Consult factory for other materials**

Series G	Frame	1/4	3/8	1/2 T	1/4 NPT	3/8 NPT	No Fitting
D/SD	2	38789	38790	38791	38792	38793	38794
	4	38789	38790	38791	38792	38793	38794

Series G	Frame	Valve	Adapter
D/SD	7	61411	
	8	61411	
G/SG	5	61411	
	6	61423	61421
	7	61423	61421

mRoy	Plunger	Valve	Adapter
A (Consult Factory)	7/16	37984	21200
	5/8	37984	21200
	1 1/16	61411	21200
S	19/32	61411	21200
RM	All	Consult Factory	
RB	All	Consult Factory	

MilRoyal	Valve
B	61411 +
C	61411 +
D	38792
G	61411 +

Centrac	Valve
B	61411 +



+ Requires head modification. Consult factory for details.

Pressures limited to 250 psi under 8 GPH

Pressures limited to 175 psi over 8 GPH

Available for PVC heads only. For others, consult factory.

